



PRO - TECHSM

INDUSTRIAL

RED SILICONE GASKET MAKER

- 100% R.T.V. Silicone-Industrial Strength
- Pressurized dispensing makes any size or shape gasket instantly
- Remains permanently flexible-temperature range -60°F to +450°F
- Reduces inventory - eliminates need to stock conventional gaskets
- Reduces down time - gets equipment back in operation fast

FORMS IN-PLACE GASKETS FOR:

- Oil & transmissions pans
- Oil & water pumps
- Valve & timing chain covers
- Gear boxes
- Machine covers
- Compressors
- Electric motors & electrical control boxes

Uses

Sealant-Adhesive can be used on metal, glass, ceramics, wood, rubber and most plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt & metal gaskets. Will not sag or shrink and is impervious to temperature extremes.

NOT RECOMMENDED FOR USE ON: Cylinder heads, exhaust manifolds, intake manifolds, carburetors, or continuous immersion in gasoline.

Specifications

Packaged:12 aerosol cans per case

Compositional information:Contains Dimethylsiloxane (CAS#70131-67-8); Amorphous Silica (CAS#7631-86-9); Methyl Triacetoxysilane (CAS#4253-34-3); Ethyl Triacetoxysilane (CAS#17689-77-9), Polydimethylsiloxane (CAS#63148-62-9).

Directions

Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surface, encircling all bolt holes. For adhesion to both parts, assemble immediately. One part adhesion, allow 10 to 15 minutes for bead to skin. Assemble parts, but do not squeeze gasket out by over tightening bolts. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Do not puncture or incinerate container. Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F. Use with adequate ventilation. Product releases acetic acid (vinegar-like odor) during curing. Contact lens wearers take appropriate precautions. Avoid breathing spray mist and vapor. Keep out of eyes. Wear eye protection while using. Avoid contact with skin. Wear rubber gloves or other nonporous hand protection while working with materials. This product is intended for industrial and commercial use and storage by trained service persons only. Manufacturer will not be responsible for any injury, loss or damage if product is used in any manner not in compliance with label directions or if precautions are not observed.

First Aid

EYES: If sprayed in eyes, flush thoroughly with large amounts of water for 15 minutes. Get medical help. **IF SWALLOWED:** Do not induce vomiting. Immediately call a physician. For skin contact, wipe off with paper towel or cloth and wash with soap and water.

Read Material Safety Data Sheet before using

MSDS is available through our web site - www.prod-chem.com