



PRO - TECHSM

INDUSTRIAL

CUTTING & TAPPING FLUID

Cools & Lubricates

WORKS WELL IN:

- SAWING • CUTTING
- BORING • GRINDING
- TAPPING • MACHINING
- PUNCHING

USE ON:

**All Steels and
Ferrous Metals**

Features

- Thick foaming oil clings to all cutting tools, preventing waste and overspraying
- Foam breaks to a heavy fortified cutting oil that resists runoff and breakdown
- Prevents chip welding -- eliminates dangerous and costly tool breakage -- contains anti-bonding agent
- Increases tool life -- stay cool under high loads
- Decreases friction for faster, more efficient cutting

Specifications

Packaged:12 aerosol cans per case

Compositional information:Contains Naphthenic Distillate (CAS#64742-52-5); Petroleum Oil (CAS#68815-10-1); Propane (CAS#74-98-6); Isobutane (CAS#75-28-5); n-Butane (CAS#106-97-8).

Directions

Spray at room temperature. Spray directly on work area from a distance of 8-10 inches. Apply to cutting tool and work place while in operation. Respray often to keep tools cool and well lubricated.

Precautions

DANGER: DO NOT SPRAY NEAR HEAT, SPARKS OR OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN. Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal. Do not take internally. Keep out of eyes. Avoid frequent or prolonged contact with skin and eyes. Do not puncture or incinerate container. Do not store at temperatures above 120°F. Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. This product is intended for industrial and commercial use and storage by trained service persons only. Manufacturer will not be responsible for any injury, loss or damage if product is used in any manner not in compliance with label directions or if precautions are not observed. For chemical emergency, spill, leak, fire, exposure or accident, call 1-800-535-5053.

First Aid

EYES: If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical help.
IF SWALLOWED: Do not induce vomiting. Immediately call a physician. For skin contact, wash with soap and water. Provide oxygen or fresh air if overcome by vapor.

Read Material Safety Data Sheet before using

MSDS (2197) is available through our web site - www.prod-chem.com