



# PRODUCTS CHEMICAL

## ACRYLIC CONCRETE SEALER

Water Based UV Resistant Non Flammable



### PRODUCT CHARACTERISTICS

- **Water Based acrylic floor sealer**
- Non Flammable
- Easily Applied - ready to use, no mixing
- Low odor and fast drying
- Approved for indoor and outdoor use
- Excellent resistance to motor oil, bearing grease, transmission fluid and road salt
- Non yellowing. UV resistant
- Good adhesion. Good durability inside and outside
- Can be recoated year after year. Simply clean and reapply.

### COVERAGE

First Coat . . . . . 1200-1500 sq ft per gallon  
Second Coat . . . . . 1500-1800 sq ft per gallon  
Third Coat . . . . . 2000+ sq ft per gallon

Refer to product label and SDS for additional information

@ 2010 Products Chemical Company All rights reserved



## **SURFACE PREPARATION**

**New concrete (after 30 days):** If an acrylic floor seal and cure was used, clean the surface with a neutral cleaner and rinse well. Apply this product 24 hours later. If a different sealer has previously been used, acid etch or chemical abrade the surface. A clear water rinse is required.

**Open concrete:** Make sure surface is free of any dirt, dust, or debris, and that the surface is clean. Apply as directed.

**Old concrete:** Remove any dirt, dust or debris. Clean surface well with neutral cleaner, using a red or green scrubbing pad. Rinse well with clean water and allow to dry a minimum of 24 hours before coating surface.

**Substrate:** Can be applied on shipping docks, warehouse floors, basements, driveways, paver sidewalks, bricks and vertical surfaces, grocery back rooms and food prep areas. Must be dry and clean.

## **METHOD OF APPLICATION**

1. Apply finish using a lambs wool applicator or T-Bar, or by spraying.
2. Apply finish in thin evenly spread coats.
3. Allow one hour dry time between coats.

## **DRY TIME**

Dry time between coats is typically 1 hour. More dry time may be needed if very humid. Allow sealer to cure for 3 days before letting cars or heavy equipment on it.

## **OUTDOOR APPLICATION**

Apply preferably in the late morning or early afternoon to avoid film formation problems due to environmental moisture. Temperature of the surface must be between 50 - 95° F.

## **PRECAUTIONS**

Keep out of reach of children. Do not take internally. Keep out of eyes. Avoid prolonged skin contact. Harmful if swallowed. To avoid contamination, do not return used material to original container. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label direction or if precautions are not observed.

**6400 Herman Avenue  
Cleveland Ohio, 44102  
216.281.1155  
www.prod-chem.com**