

PRODUCTS CHEMICAL BIG 10 SEALER

ULTRA Oil Modified Urethane Seal



This sealer is designed to be used in conjunction with Urethane Finish. The lower solids content enables excellent sealer penetration. We recommend that new and sanded floors be sealed with this product prior to applying the finish. When used in conjunction with a Urethane Finish, this sealer will provide a base coat for a high gloss, durable, long wearing surface.

***Beautify, rejuvenate, protect and extend floor life
-- all with one product.***

High gloss for increased light reflection

- Easily applied - ready to use, no mixing
- Extends floor life - high abrasion and impact resistance
- Light in color
- Quick Dry
- Will not yellow with age
- Excellent penetration



OIL MODIFIED URETHANE COATING

DESCRIPTION

A superior oil modified urethane sealer that combines high gloss with tough durability. This product has outstanding leveling characteristics, resistance to yellowing, abrasion, chemicals, etc.

This product previously met the USDA standards for use in Federally inspected meat and poultry plants. Meets or exceeds all MFMA specifications.

COVERAGE

Coverage 400 - 600 square feet per gallon

DRY TIME

Drying Time 3 - 4 hours

SURFACE PREPARATION

1. New or sanded floor surface should be clean and dry.
2. Floor should be vacuumed and tacked with Waterless Cleaner 2702 to remove excess dust.

METHOD OF APPLICATION

1. Apply sealer using a lambs wool applicator, roller, or T-bar.
2. Place sealer in applicator pan, dip applicator into finish. FLOW ON IN THIN COATS. Spread evenly.
3. Allow to dry.
4. A Urethane finish should be applied over surface.

TECHNICAL DATA

Weight per gallon	7.2 pounds
Voc	<350 g/l
Solids	35%
Clarity	Clear & Sharp
Resistance to Skinning	Good
Flash Point	Over 100 F
Slip Resistance	Excellent
Suitability for Waxing	Excellent
Initial Gloss	Very High
Color Retention	Excellent
Gloss Retention	Excellent

Refer to product label and SDS for additional information.
©2003 Products Chemical Company. All rights reserved.

**6400 Herman Avenue
Cleveland Ohio, 44102
216.281.1155
www.prod-chem.com**