



PRODUCTS CHEMICAL

CELEBRITY HIGH SOLIDS FLOOR FINISH & SEAL

DESCRIPTION

The floor finish for the new century. Non-yellowing. Non-powdering. Floors stay looking sharp and clean even under heavy foot traffic.

GIVES FLOORS A TOUGH, BRILLIANT LOOK

Industrial strength. Urethane fortified. Can be furnished with high speed equipment, if desired. Produces a durable finish that stands up to heavy traffic.

WITHSTANDS ALL TYPES OF CONDITIONS

Works well in all applications. Industrial strength. Urethane fortified. Provides Ultimate in responsiveness, repair-ability and durability. Resists stains. Impervious to grease and oil. Resists scuffing and heel marks. Slip resistant. Will not harm anti-static floors or affect their effectiveness.

PROFESSIONAL RESULTS

Micron-size particles penetrate deep to fill the smallest pores giving an armor-tough cohesive bond to the floor surface. Self-leveling agents give a uniform, crystal clear gloss with little effort.

SIMPLE TO USE

Compatible with ALL standard finishes. Just scrub and apply for a deep, high-solids gloss.



**6400 Herman Avenue
Cleveland Ohio, 44102
216.281.1155
www.prod-chem.com**

DESCRIPTION

An industrial grade long-lasting floor finish. The ultra high solids floor finish is self-sealing. The urethane fortified acrylic polymer finish provides a deep, durable gloss that will not yellow, discolor or powder, even with high speed burnishing. Fewer coats of this floor finish needed immediately reduces not only material costs, but more importantly reduces labor-application costs. Can be used on all types of floors and is extremely resistant to scuffing, detergent cleaning and staining.

APPLICATION

For use on most composition and hard surface floors:
Floors, Schools, Motels, Factories, Terrazzo, Offices, Laundries, Garages,
Concrete, Painted Surfaces, Plants, Hotels, Restaurants, Plastic

DIRECTIONS FOR USE

- Clean floor thoroughly with STRIPPER or heavy duty cleaner/ degreaser.
- Rinse floor well and let dry.
- Apply FLOOR FINISH freely with clean mop or wool applicator.
- Let floor dry at least 1/2 hour (longer, in high humidity).
- Apply thin second coat to assure thorough sealing. Let dry.

SPECIFICATIONS

Packaged: Drums, 5- gallon pails, 4- 1 gallons
Appearance: Milky liquid
Fragrance: Characteristic
pH:8.00
Flash Point:None. Nonflammable
Coverage:1500 square feet per gallon
Dry Time: 20-30 minutes per coat
Static coefficient of friction:meets or exceeds 0.5 as
determined by ASTM method D2047-82

PRECAUTIONS

Keep out of reach of children. Do not take internally. Keep out of eyes. Avoid prolonged skin contact. Harmful if swallowed. To avoid contamination, do not return used material to original container. Rinse empty container with water and discard. This product is intended for industrial and commercial use and storage. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label direction or if precautions are not observed.

FIRST AID

EYES: Flush with large amounts of water for at least 15 minutes. Contact physician if irritation persists. IF SWALLOWED: Do not induce vomiting or give anything by mouth to an unconscious person. Seek medical attention. EXTERNAL: Flush with large amounts of water.