

PRODUCTS CHEMICAL

GREENFIELDS FLOOR FINISH



This product has been approved by the U.S. EPA's Design for the Environment program and will help you achieve your green cleaning goals.

WITHSTANDS ALL TYPES OF CONDITIONS

Works well in all applications. Industrial strength. Use on all types of resilient tile flooring and properly prepared hard surfaces to provide a durable finish that can be maintained with standard scrub and recoat procedures, spray buffing and high speed burnishing. Provides ultimate in responsiveness, repairability and durability. Resists stains. Impervious to grease and oil. Resists scuffing and heel marks. Slip resistant.

Refer to product label and SDS for additional information

© 2011 Products Chemical Company All rights reserved

PROFESSIONAL RESULTS EVERYTIME

Micron-size particles penetrate deep to fill the smallest pores giving an armor-tough cohesive bond to the floor's surface. Self-leveling agents give a uniform, crystal clear gloss with little effort.



Recognized for Safer Chemistry
www.epa.gov/dfe



DESCRIPTION

An industrial grade long-lasting green floor finish that is DfE approved. This zinc-free, low odor, phthalate-free finish provides a deep, durable gloss that will not yellow, discolor or powder, even with high speed burnishing. Can be used on all types of floors and is extremely resistant to scuffing, detergent cleaning and staining.

APPLICATION

For use on most composition and hard surface floors.
Floors, Schools, Motels, Factories, Terrazzo, Offices, Laundries, Garages,
Concrete, Painted Surfaces, Plants, Hotels, Restaurants, Plastic

DIRECTIONS FOR USE

- Clean floor thoroughly with STRIPPER or heavy duty cleaner/degreaser.
- Rinse floor well and let dry.
- Apply FLOOR FINISH freely with clean mop or wool applicator.
- Let floor dry at least 1/2 hour (longer, in high humidity).
- Apply thin additional coats to assure thorough sealing. Let dry.

SPECIFICATIONS

Packaged: Drums, 5- gallon pails, 4- 1 gallons
Appearance: Milky liquid
Fragrance: Characteristic
pH: 8.00
Flash Point: None. Nonflammable
Coverage: 1500 square feet per gallon
Dry Time: 20-30 minutes per coat
Static coefficient of friction: meets or exceeds 0.5 as
determined by ASTM method D2047-82

PRECAUTIONS

Keep out of reach of children. Do not take internally. Keep out of eyes. Avoid prolonged skin contact. Harmful if swallowed. To avoid contamination, do not return used material to original container. Rinse empty container with water and discard. This product is intended for industrial and commercial use and storage. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label direction or if precautions are not observed.

FIRST AID

EYES: Flush with large amounts of water for at least 15 minutes. Contact physician if irritation persists. IF SWALLOWED: Do not induce vomiting or give anything by mouth to an unconscious person. Seek medical attention. EXTERNAL: Flush with large amounts of water.