



PRODUCTS CHEMICAL

HEAVY DUTY STRIPPER

NON-AMMONIATED
FLOOR FINISH
STRIPPER

HEAVY DUTY STRIPPER

A new heavy duty stripper used for stripping both metal- interlock floor finish and acrylic undercoat floor sealers. Stripper is especially unique in that it is non-ammoniated. This feature makes the stripper ideally suited for use in hospitals, nursing homes and supermarkets.

EVAPORATION CONTROL

Stripper's controlled evaporation ingredients hold old finishes on surface longer to help prevent redepositing and drying.

PLEASANT TO USE

Non-ammoniated formula makes stripping floors a less dreadful task. Work area does not have to be evacuated by employees, patients, or customers since stripper does not have the strong ammonia odor of ordinary strippers.

BETTER FOR FLOOR SURFACE

Since heavy duty stripper contains no ammonia, color bleeding is limited and floors retain their original beauty longer.

Quick-acting, literally dissolves the finish or sealer that is being stripped. Requires very little agitation. Saves time and money.

DESCRIPTION

Heavy duty stripper is especially formulated to remove all types of waxes and finishes from all kinds of floors. Stripper works in a new way to penetrate quickly the most stubborn wax and polymer-finish films so they can be more readily removed. Good floor care begins with a completely clean floor. The outstanding appearance of a finished floor is well worth the extra initial attention of preparing a floor. The old wax or finish must be completely removed and the floor well-cleaned and rinsed.

APPLICATION

For use on all types of floors including:

Asphalt, Concrete, Marble, Quarry tile, Stone, Rubber, Terrazzo, Vinyl, Vinyl Asbestos, Ceramic tile

DIRECTIONS FOR USE

Mix stripper with warm (not hot) water. Hard water will not hamper stripper. Use the following dilutions (expressed as 1 part STRIPPER to X parts water)
1 to 2 For floors that have been badly neglected. **1 to 5** For non-buffable, metal cross-linked polymer finishes or for very heavy buildup of finishes. **1 to 10** For buffable and water resistant waxes. **1 to 20** For non-water resistant waxes.
1 to 40 For new, previously unfinished floors to remove oily coating place there by the manufacturer.

SPECIFICATIONS

Packaged: Drums, 5- gallon Enviro-pak, 4- 1 gallons
Appearance: Green liquid
Odor: Characteristic
pH:11.50
Flash point: None. Non-flammable
Solubility in water: Complete

PRECAUTIONS

Keep out of reach of children. Do not take internally. Keep out of eyes. Avoid prolonged skin contact. Care should be taken with painted surfaces, especially water-base paints to assure that not of the paint is removed. Rinse empty container with water and discard. This product is intended for industrial and commercial use and storage by trained service persons only. Manufacturer will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label direction or if precautions are not observed.

FIRST AID

EYES: Flush with large amounts of water for at least 15 minutes; contact physician.
IF SWALLOWED: Induce vomiting. Drink large quantities of water. Seek medical attention.
EXTERNAL: Flush with large amounts of water. Remove contaminated clothes. Seek medical attention.

Products Chemical Company, LLC
6400 Herman Avenue Cleveland Ohio, 44102
216.281.1155
www.prod-chem.com